

ABS

ROYALITE®



ABS is a low cost thermoplastic material with outstanding impact resistance, machinability, and thermoforming characteristics. It is an excellent choice for machine housings, retail store fixtures, and point-of-purchase displays where impact resistance is required.

Royalite® R59 is a fire-rated ABS/PVC alloy sheet material, that is often used for transportation, architectural, and electronics applications that require UL certifications.

Royalite® R84/21 is an ABS sheet material with a proprietary weatherable cap layer for improved performance in outdoor environments. The material is an excellent choice for marine, automotive, and recreational vehicle components where good weatherability is required.



KEY CHARACTERISTICS:

- Outstanding impact resistance
- Good machinability
- Easy to thermoform
- Easy to bond with adhesives
- Strong and stiff
- Low cost
- Flame retardant grades available
- Available in a wide variety of colors and textures

APPLICATIONS:

- Display trays
- Storage cases
- Display bases
- Product holders
- Thermoformed displays
- Display components
- Models and prototypes

ABS TYPICAL PROPERTIES:

	UNITS	ASTM TEST	ABS	ROYALITE® R59	ROYALITE® R84/21
Tensile strength	psi	D-638	4,100	5,200	4,600
Flexural modulus	psi	D-790	304,000	290,000	270,000
Izod impact (notched)	ft-lbs/in of notch	D-256	7.7	10.0	7.0
Heat deflection temperature @264 psi	°F	D-648	177	170	205
Maximum continuous service temperature in air	°F		160	-	-
Water absorption (immersion 24 hours)	%	D-570	0.30	-	-
Coefficient of linear thermal expansion	in/in/°F x 10 ⁻⁵	D-696	5.6	4.6-5.5	4.2-5.6

Standard Sizes: SHEET: 24"x48" (0.25"-4.0" thick), 48"x96" (0.06"-4.0" thick) ROD: diameter 0.25"-6.0"

Length, width, thickness, and diameter tolerances vary by size and by manufacturer • Custom sizes and colors available upon request • Many of our materials are available as films with thicknesses of 0.029" or less. Values may vary according to brand name. Please ask your Curbell Plastics representative for more specific information about an individual brand.

Curbell Plastics has been supplying plastic sheet, rod, tube, films, adhesives, sealants, and prototyping materials for over 65 years



NATIONWIDE
1.888.CURBELL
www.curbellplastics.com

©2008 Curbell Plastics, Inc. All other trademarks and service marks are property of the respective manufacturers. All statements, technical information and recommendations contained in this publication are presented in good faith, based upon tests believed to be reliable and practical field experience. The reader is cautioned, however, that Curbell, Inc. cannot guarantee the accuracy or completeness of this information, and it is the customer's responsibility to determine the suitability of specific products in any given application.

ABSDataSheet 0308