


# KYDEX<sup>®</sup> THERMOPLASTIC SHEET



Photographs provided by Kleerdex Company, LLC. Copyright 2007, all rights reserved.

KYDEX<sup>®</sup> thermoplastic sheet is a proprietary material that has excellent aesthetic qualities, superior impact resistance, and outstanding formability. It is an excellent choice for thermoformed equipment housings and airplane, bus, and train interior parts where appearance, toughness, and complex thermoforming are required.



## KEY CHARACTERISTICS:

- Excellent impact resistance
- Easy to thermoform
- Strong and stiff
- Good electrical insulating properties
- Consistent color throughout material helps hide scratches and wear
- UL rated grades available
- Fire retardant grades available
- Available in a wide variety of colors and textures

## APPLICATIONS:

- Furniture components
- Shelving
- Display bases
- Kiosks
- Checkout counters
- Cabinetry
- Exhibits
- Door and drawer fascias
- Work stations
- Pedestals and stands
- Kickplates and pushplates
- Flat laminated panels of all types

## KYDEX<sup>®</sup> THERMOPLASTIC SHEET TYPICAL PROPERTIES:

Tensile strength	psi	D-638	
Flexural modulus	psi	D-790	
Izod impact (notched)	ft-lbs/in of notch	D-256	
Heat deflection temperature @264 psi	°F	D-648	
Maximum continuous service temperature in air	°F		
Water absorption (immersion 24 hours)	%	D-570	
Coefficient of linear thermal expansion	in/in/°Fx10 <sup>-5</sup>	D-696	

### Standard Sizes: SHEET: 48"x96" (0.028"-0.500" thick)

Length, width, thickness, and diameter tolerances vary by size and by manufacturer • Custom sizes and colors available upon request • Many of our materials are available as films with thicknesses of 0.029" or less. Values may vary according to brand name. Please ask your Curbell Plastics representative for more specific information about an individual brand.

Curbell Plastics has been supplying plastic sheet, rod, tube, films, adhesives, sealants, and prototyping materials for over 65 years



NATIONWIDE  
**1.888.CURBELL**  
www.curbellplastics.com

©2008 Curbell Plastics, Inc. All other trademarks and service marks are property of the respective manufacturers. All statements, technical information and recommendations contained in this publication are presented in good faith, based upon tests believed to be reliable and practical field experience. The reader is cautioned, however, that Curbell, Inc. cannot guarantee the accuracy or completeness of this information, and it is the customer's responsibility to determine the suitability of specific products in any given application. KydexDataSheet 0308