

DuPont™ Vespel® Polyimide Shapes

Authorized Supplier of Authentic
Vespel® Polyimide Shapes



Curbell PLASTICS

HIGH PERFORMANCE PARTS MADE FROM VESPEL® POLYIMIDE SHAPES:

- Provide strength and toughness to resist damage
- Withstand high temperatures
- Provide low wear and friction
- Hold tight tolerances
- Are first-class electrical insulators
- Have excellent machinability
- Resist chemical attack
- Offer high purity and low out-gassing



semiconductor • aerospace • high temperature applications



Put us to work – for you!™

Curbell Plastics has been supplying plastic sheet, rod, tube, films, adhesives, sealants, tapes, prototyping and tooling materials, and fabricated parts for over 65 years

ALBANY
800.553.0335

CLEVELAND
800.223.2725

FLORIDA
888.388.3417

PHOENIX
800.227.7963

SYRACUSE
800.446.4624

TAPES & FABRICS
888.287.2355

ATLANTA
800.433.9756

COLORADO
866.319.8723

NEW ENGLAND
800.637.2763

PITTSBURGH
800.548.0650

VIRGINIA
888.349.8897

FILMS GROUP
888.287.2355

CINCINNATI
800.334.9699

DETROIT
800.354.4798

PHILA & NJ
800.831.2550

ROCHESTER
800.722.2140

WESTERN NY
800.544.1498

CORPORATE OFFICE
716.667.3377



CURBELL PLASTICS, INC.

NATIONWIDE 1.888.CURBELL
www.curbellplastics.com

DuPont™ Vespel® Polyimide Shapes

Vespel® S Line offers Highly Durable, Versatile Polyimides

Vespel® shapes are available in five compositions of SP polyimide resin including an unfilled grade, Vespel® SP-1, and several low wear bearing grades: Vespel® SP-21, SP-22, SP-211, and SP-3.

Vespel® SP-1 for Physical and Electrical Properties

SP-1, the unfilled base resin (high purity), provides maximum physical strength, elongation, and toughness and the best electrical and thermal insulation properties. Semiconductor manufacturers often find components fabricated from Vespel® SP-1 shapes useful in production processes.

Vespel® SP-21 for Balanced Low Wear and Physical Properties

SP-21 has 15% graphite, by weight, added to the base resin for low wear and friction in applications such as bearings, thrust washers, bushings, seal rings, slide blocks, and other wear surfaces. SP-21 has the maximum physical strength, elongation, and toughness of the graphite filled resins.

Vespel® SP-22 for Low Wear and Dimensional Stability

SP-22 has 40% graphite, by weight, added to the base resin providing enhanced resistance to wear and friction as well as improved dimensional and oxidative stability. SP-22 has the lowest coefficient of thermal expansion.

Vespel® SP-211 for Low Coefficient of Friction and Unlubricated Wear Resistance

SP-211 has 10% TEFLON® resin and 15% graphite, by weight, added to the base resin to provide the lowest coefficient of friction over a wide range of operating conditions. It offers excellent wear resistance up to 300°F (149°C).

Vespel® SP-3 for Unlubricated Sealing and Low Wear in Vacuum or Dry Environments

SP-3 has 15% molybdenum disulfide (MoS₂), by weight, added to the base resin to provide lubrication for seals and bearings in vacuum or dry environments. SP-3 provides maximum wear and friction resistance in vacuum and other moisture-free environments, where graphite actually becomes abrasive.

Vespel® SCP-5000 for Strength, Hardness, and Chemical Resistance over Broad Temperature Range

SCP-5000 is an unfilled polyimide copolymer developed for demanding applications that require toughness, thermal and dimensional stability, chemical resistance, and stable dielectric performance across a broad temperature range.



wafer handling • seals • valves • fasteners gears • splines
thrust washers • wear pads compressor and pump parts
piston rings • bushings • bearings • hot glass handling

PROPERTY	METHOD	TEMP (°F)	UNITS	SP-1	SP-2	SP-22	SP-211	SP-3	SCP-5000
Tensile Strength (Ultimate)	ASTM D-638/ D-1708	73 500	psi psi	12,500	9,500	7,500	6,500	8,200	23,400
				6,000	5,500	3,400	3,500	-	9,000
Elongation (Ultimate)	ASTM D-638/ D-1708	73 500	% %	7.5	4.5	3.0	3.5	4.0	7.0
				7.0	2.5	2.5	3.0	-	>20
Flexural Modulus	ASTM D-790	73 500	psi psi	450,000	550,000	700,000	450,000	-	836,000
				250,000	370,000	400,000	200,000	-	436,000
Compressive Modulus	ASTM D-695	73	psi	350,000	420,000	475,000	300,000	-	1,330,000
Wear Rate (PV=25,000)	Unlub.	-	in/1000 hours	0.25-1.20	0.09	0.06	0.07	0.25-0.33	-
Friction Coefficient	Unlub.	-	-	0.29	0.24	0.20	0.12	0.25	0.26
				0.35	0.30	0.27	0.20	-	-
				-	-	-	-	0.03	-
Coefficient of Linear Thermal Expansion	D-696	73-500	10 ⁻⁶ in/in°F	30	27	21	30	-	26
Dielectric Constant	D-150	73	@10 ⁴ Hz	3.64	13.28	-	-	-	3.31

Underwriters Laboratory Flame Rating: 94-V0

Our material partner  *The miracles of science™*

For a complete list of addresses, contact information, materials, or to request a quote please visit our website: www.curbellplastics.com

Authorized Supplier of Authentic Vespel® Polyimide Shapes

 **NATIONWIDE 1888.CURBELL**
www.curbellplastics.com

©2009 Curbell Plastics, Inc. The DuPont Oval Logo, DuPont, The miracles of science and Vespel®, Teflon®, and Delrin® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. CAUTION: Vespel® is not permitted for use in medical applications involving any implantation in the human body or where contact with internal body fluid or tissues will equal or exceed 24 hours. All other trademarks and service marks are property of the respective manufacturers. All statements, technical information and recommendations contained in this publication are presented in good faith, based upon tests believed to be reliable and practical field experience. The reader is cautioned, however, that Curbell Plastics, Inc. cannot guarantee the accuracy or completeness of this information and it is the customer's responsibility to determine the suitability of specific products in any given application.

MAP0157B 0809