



Tape Solutions for Heat Sealing



Tape Solutions for Heat Sealing

Saint-Gobain® offers a complete range of **CHR®** PTFE Adhesive Tapes to perform in a variety of heat seal packaging processes involving impulse heat sealers and hot bar sealers. **CHR** heat sealing tapes provide a non-stick, abrasion resistant surface designed for use in high temperature heat sealing applications. These highly durable tapes allow for increased process speeds and minimal down time increasing overall process efficiency. Different backings and adhesive systems are combined to offer a variety of solutions that balance cost and performance.

Heat Sealing Tapes

Products: PTFE Glass Laminate Tape, PTFE Glass Cloth Tape, Zone Tape, Extruded PTFE Tape, Enhanced High Modulus PTFE Tape, Filled PTFE Tape

Function: Release surface for packaging plastics

Features: Non-stick surface, wear resistance, temperature resistance, dimensional stability, PTFE Glass Cloth for tear resistance

PTFE Glass Laminate Tape: **CHR** SGB6 and SGC6 **Chemlam®** are premium solutions for heat seal packaging. A proprietary manufacturing method allows these products to have fewer defects such as cracks and pinholes. The more consistent release surface and higher PTFE thickness over the glass gives these products longer life and more cycles compared to lower grade options. This allows users to operate more efficiently with less down time spent changing release tapes.

PTFE Glass Cloth Tape: PTFE is coated onto glass fabric to enhance dimensional stability, tear strength, and abrasion resistance while maintaining a non-stick surface. Several different grades are available at various PTFE coating weights to offer economic options or high performance solutions for smoother seals and increased durability. **CHR** SG25 series is the most commonly used solution because it offers a balance between cost and performance. In addition to silicone adhesive, acrylic is available for application temperatures under 350°F where higher bond strength is desired.

Aluminum PTFE Foil Tape: **CHR** MD15 is PTFE laminated to aluminum foil. The lamination construction gives the tape longer life in application and can be run at faster speeds due to improved thermal conductivity. The metal construction can be detected by X-ray and metal detectors on food packaging lines that detect foreign contamination.

Zone Tape: **CHR** 2829 is made from PTFE coated glass fabric with selective adhesive placement. Adhesive can be placed only where needed to keep it away from the heating element for hot wire sealers.

Extruded PTFE Tape: These tapes are made of 100% extruded PTFE film backing. The additional PTFE content compared to glass reinforced products allows for extended life in narrow heat sealing applications where dimensional stability is not as critical. **CHR** 2275, 2283, and 2285 are brightly colored products that can be seen clearly against the metal platen they are adhered to. **CHR** 2283 is an acrylic adhesive option for lower temperature heat sealing processes (<350°F). The 2 mil thickness of these products improves heat transfer allowing for faster line speeds.

High Modulus PTFE Tape: **CHR** R233 and R253 are made with 3 mil high modulus PTFE films. The increased PTFE backing thickness increases longevity over thinner extruded tape options. **CHR** R233 has an acrylic adhesive system for higher adhesive strength while **CHR** R253 is designed for use in higher temperature heat sealing processes. **CHR** 22B5-2 and 22B5-2HA are made with a 2.2 mil anti-static high modulus backing. The substrate is designed for abrasion resistance needed for heat sealing and roller wrap applications. **CHR** 22B5-2 resists movement in high shear PE extrusion applications and 22B5-2HA offers high adhesion desired in heat sealing to prevent edge curl.

Filled PTFE Tape: **CHR Rulon®** Tape will last the longest as a release surface in heat sealing processes compared to the rest of the **CHR** tape portfolio. It is made from a thick PTFE backing that contains special fillers designed to maximize abrasion resistance and product life. **CHR** RU and RU101 can last up to 20 times as long as standard PTFE glass heat seal tapes saving both time and money from improved process efficiency.

Heat Sealing Tapes

Backing Material	Substrate Grade	Adhesive	Tape Backing Thickness							Operating Temperature °F (°C)	Product Features	
			Product Code									
			0.002 in (0.050 mm)	0.003 in (0.076 mm)	0.004 in (0.102 mm)	0.005 in (0.127 mm)	0.006 in (0.152 mm)	0.008 in (0.203 mm)	0.010 in (0.254 mm)			0.014 in (0.356 mm)
PTFE Glass Cloth Laminate	Chemlam	Silicone			SGB6-4		SGC6-6		SGB6-10		-100 to 500 (-73 to 260)	Features Chemlam backing for maximum life
PTFE Aluminum		Silicone		MD15							-100 to 500 (-73 to 260)	Metal detectable
PTFE Glass Cloth	High Performance	Silicone		A2005							-100 to 500 (-73 to 260)	High temperature adhesion
PTFE Glass Cloth	High Performance	Silicone				SG16-05					-100 to 500 (-73 to 260)	High performance, long life & clean release adhesive
PTFE Glass Cloth	High Performance	Silicone		SG15-03		SG15-05	SG15-06			SG15-14	-100 to 500 (-73 to 260)	High performance, long life
PTFE Glass Cloth	Premium	Acrylic		SG03-03							-40 to 350 (-40 to 177)	Premium, long life & high adhesion
PTFE Glass Cloth	Premium	Silicone		SG05-03		SG05-05	SG05-06		SG05-10		-100 to 500 (-73 to 260)	Premium & long life
PTFE Glass Cloth	Primary	Acrylic				SG23-05				SG23-10	-40 to 350 (-40 to 177)	Balanced life, cost & high adhesion
PTFE Glass Cloth	Primary	Silicone		SG26-03		SG26-05					-100 to 500 (-73 to 260)	Balanced life, cost & clean release adhesive
PTFE Glass Cloth	Primary	Silicone		SG25-03		SG25-05	SG25-06		SG25-10		-100 to 500 (-73 to 260)	Balanced life & cost
PTFE Glass Cloth	Industrial	Silicone		SG35-03		SG35-05	SG35-06		SG35-10		-100 to 500 (-73 to 260)	Economical grade
PTFE Glass Cloth		Acrylic		2829-03		2829-05					-40 to 350 (-40 to 177)	Zone tapes with selective adhesive placement
Extruded PTFE		Acrylic	2283-2								-40 to 350 (-40 to 177)	High adhesion & high heat transfer & easy to detect wear
Extruded PTFE		Silicone	2265-2, 2275-2, 2285-2								-100 to 500 (-73 to 260)	High heat transfer & easy to detect wear
High Modulus		Silicone	22B5-2								-100 to 500 (-73 to 260)	Resists movement, designed for roller wrap applications & anti-static
High Modulus		Silicone	22B5-2HA								-100 to 500 (-73 to 260)	High adhesion & anti-static
Enhanced High Modulus PTFE		Acrylic		R233							-40 to 350 (-40 to 177)	High adhesion & thick PTFE layer
Enhanced High Modulus PTFE		Silicone		R253							-100 to 500 (-73 to 260)	Thick PTFE layer
Filled PTFE		Acrylic						RU101			-40 to 350 (-40 to 177)	High wear resistance & high adhesion
Filled PTFE		Silicone						RU			-100 to 500 (-73 to 260)	High wear resistance

Your Partner in Custom Tape Solutions

A custom tape solution can pay for itself many times over thanks to the process and product improvements it can provide. Tape development engineers will work with partners to design an economical but highly effective tape product.

Even with endless permutations of industrial tapes available there is only one company that can deliver a custom-made tape with optimal adhesive, the perfect backing materials, seamless process integration and superb performance.

To learn more about how **Saint-Gobain** can help solve tape and materials engineering challenges, call us or visit us online.

Distributed by:



Curbell Plastics is a proud supplier of Saint-Gobain Tape Solutions

Scan to visit our website:



Saint-Gobain Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit
tapesolutions.saint-gobain.com/contact-us

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1548 | © Saint-Gobain November 2020 | **CHR, Chemlam** and **Rulon** are trademarks of **Saint-Gobain**.