

# CHR<sup>®</sup> 2925/2995

## Glass-Foil Pressure Sensitive Adhesive Tape

**CHR 2925** and **2995-11R** are manufactured from aluminium foil laminated to fibreglass cloth with high-temperature silicone adhesive on one side.

### Features/Benefits

**CHR 2925's** high-temperature silicone adhesive allows the product to withstand continuous high temperatures, and prevents tape slippage after application. **CHR 2995-11R** is formed by laminating 0.127 mm (5.0 mil), dead soft aluminium foil to fibreglass fabric and applying a special blend of high-temperature silicone adhesives. The backing provides an excellent combination of strength, flexibility and heat resistance. Both **2925** and **2995-11R** have excellent strength and flexibility, which provides easy wrapping of complex shapes and minimizes wrinkling.



### Availability

**CHR 2925** is available in 0.178 mm (7.0 mil) and 0.279 mm (11.0 mil) thicknesses, factory stock is in master rolls 33 m × 914 mm (36 yd × 36 in), and rolls can be slit in widths ranging from 6.35 mm to 914 mm (0.25 in to 36 in). **CHR 2925** is available with or without a liner. **CHR 2995-11R** is supplied on a clear polyester release liner. It unwinds easily, can be die-cut, and each roll is started with a pull-tab. Factory stock for **2995-11R** is in master rolls 33 m × 914 mm (36 yd × 36 in), and rolls can be slit in widths ranging from 12.7 mm to 914 mm (0.5 in to 36 in).

### Applications

**CHR 2925** performs as a plasma or flame spray masking tape, allowing areas to be free of grit blasting and the plasma spray coating. Its high-temperature resistance makes it ideal for heat and reflectant tapes, and it is used in aerospace and automotive markets as a wire harness bundling tape in engine components. **CHR 2925** also is used as a sound and vibration dampening product. **CHR 2995-11R** is designed for extremely high demand thermal spray applications, such as HVOF and High Detonation Systems. It provides excellent abrasion and temperature resistance and conforms very well to a wide variety of surface configurations. The extremely aggressive adhesive system assures the tape stays in place throughout the entire coating process and will release cleanly after use, reducing the cleaning of the coated parts.

## CHR 2925/2995 Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	2925-7	2925-11	2995-11R
Backing Material	Glass-Foil	Glass-Foil	Glass-Foil
Adhesive Type	Silicone	Silicone	Silicone
Total Thickness mm (mil)	0.178 (7.0)	0.279 (11.0)	0.305 (12.0)
Backing Thickness mm (mil)	0.064 (2.5)	0.191 (7.5)	0.178 (7.0)
Adhesive Thickness mm (mil)	0.114 (4.5)	0.089 (3.5)	0.127 (5.0)
Adhesion to Steel N/cm (oz/in)	6.6 (60)	8.2 (75)	4.9 (45)
Tensile Strength N/cm (lb/in)	228 (130)	350 (200)	263 (150)
Elongation (% at break)	7	7	5
Operating Temperature °C (°F)	-73 to +260 (-100 to +500)	-73 to +260 (-100 to +500)	-73 to +260 (-100 to +500)
Colour	Aluminium	Aluminium	Aluminium



### Saint-Gobain Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit  
[tapesolutions.saint-gobain.com/contact-us](http://tapesolutions.saint-gobain.com/contact-us)

**CURBELL**  
PLASTICS

1-888-CURBELL

[www.curbellplastics.com](http://www.curbellplastics.com)

Curbell Plastics is a proud supplier of Saint-Gobain Tape Solutions

**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

**WARRANTY:** For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1135 | © Saint-Gobain July 2020 | **CHR** and **CHRTape** are trademarks of Saint-Gobain.