

CHR[®] SGC6

PTFE Coated Glass Cloth Tapes

Saint-Gobain[®] CHR Tape SGC6 is a copper fiberglass fabric impregnated with Polytetrafluoroethylene (PTFE) dispersion and coated with a high temperature, pressure sensitive silicone adhesive.

Features/Benefits

SGC6 is a laminate construction offering an additional 0.001" (1 mil) of **Chemlam[®]** PTFE over the entire surface of the impregnated cloth, delivering a product with exceptional durability and longevity. The combination of uniform and pin-hole free film enables SGC6 to outperform thicker PTFE-coated fiberglass tapes. SGC6 is dimensionally stable and resistant to tears, punctures, abrasion and wear.

Availability

SGC6 is available in 4, 6 and 10 mil thicknesses and widths from 6.35 to 914.4 mm (0.25 to 36 in). Standard roll length is 16 or 33 m long (18 or 36 yd). SGC6 is available with or without a liner.

Applications

CHR SGC6 is frequently used by the packaging industry as a release surface on heat sealers, blister formation and form-fill equipment where heavy production demands a product with more release surface material. The durability and anti-stick properties of SGC6 also make it an ideal material for the lining of guide rails, chutes and slides. The high temperature capabilities and non-stick properties of SGC6 allow it to perform as an excellent release surface in severe industrial environments, platen covers, dry can covers and the composite aircraft industry.



CHR SGC6 Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	SGC6-04	SGC6-06	SGC6-10
Backing Material	PTFE Coated Fiberglass Fabric	PTFE Coated Fiberglass Fabric	PTFE Coated Fiberglass Fabric
Adhesive Type	Silicone	Silicone	Silicone
Total Thickness mm (mil)	0.160 (6.3)	0.201 (7.9)	0.290 (11.4)
Backing Thickness mm (mil)	0.109 (4.3)	0.150 (5.9)	0.239 (9.4)
Adhesive Thickness mm (mil)	0.051 (2.0)	0.051 (2.0)	0.051 (2.0)
Adhesion to Steel N/cm (oz/in)	5.0 (45)	5.5 (50)	6.0 (55)
Elongation (% at break)	<5	<5	<5
Operating Temperature °C (°F)	-73 to +260 (-100 to +500)	-73 to +260 (-100 to +500)	-73 to +260 (-100 to +500)
Color	Copper	Copper	Copper

**Saint-Gobain Tape Solutions**

North America | South America | Europe | Asia

For a full list of locations, please visit
tapesolutions.saint-gobain.com/contact-us

CURBELL
PLASTICS

1-888-CURBELL

www.curbellplastics.com

Curbell Plastics is a proud supplier of Momentive materials

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1528 | © Saint-Gobain July 2020 | **CHR** and **Chemlam** are trademarks of Saint-Gobain.