

Cyberbond

UNDO 6020 TECHNICAL DATA SHEET

The Power of Adhesive Information
cb
Cyberbond™

UNDO 6020 cyanoacrylate adhesive remover quickly softens and dissolves adhesive from unwanted areas. UNDO 6020 is an essential product for industrial manufacturing and production involving the use of cyanoacrylates.

Physical Properties - Liquid

Base Compound	Nitromethane
Appearance	Colorless liquid
Viscosity	1 cps
Specific Gravity	1.1 g/cc
Flash Point	96°C
Shelf Life	18 months unopened
Boiling Point	214°F
Odor	Mild
Vapor Density	Heavier than air
Percentage Volatiles (by weight)	not available
RoHS Compliant?	Yes

General Instructions

Used in the removal from metal, plastic, and rubber surfaces. Allow several minutes after application of UNDO 6020 before cleaning or wiping away from substrate surface. Depending on the quantity of adhesive being removed, additional applications of UNDO 6020 may be necessary. When attempting to remove bonded parts, soaking them for an extended time may be necessary.

NOTE: May adversely affect some plastics and other materials. Test First.

Storage

UNDO 6020 is highly flammable and should be stored away from heat, open flame, or ignition sources. Products should be stored unopened in a cool, dry place out of direct sunlight.

Health Precautions

Skin Contact: Wash exposed areas with copious amounts of soap and water for 15-20 minutes.

Prior to use: See Material Safety Data Sheet

Curing Performance

Not applicable

Specifications and Approvals

None

Note

The data contained herein are furnished for information only and are believed to be reliable. Cyberbond L.L.C. cannot assume responsibility for the results obtained by others over whose method Cyberbond L.L.C. does not control. It is the user's responsibility to determine suitability for the product or of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Cyberbond L.L.C. specifically disclaims all warranties of merchantability or fitness for a particular purpose arising from sale or use of Cyberbond L.L.C. products. Cyberbond L.L.C. specifically disclaims any liability for consequential or incidental damages of any kind, including loss of profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Cyberbond L.L.C. patents which may cover such processes or compositions. We recommend that each prospective user test the proposed application to determine its suitability for the purpose intended prior to incorporating any product or application in its manufacturing process using the data as a guide.

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS)

Cyberbond, LLC
401 N Raddant Road
Batavia, IL 60510
630.761.8900 tel
www.cyberbond1.com

Cyberbond Europe GmbH
Werner-von-Siemens Straße 2
D - 31515 Wunstorf
Germany
49 / 50 31 / 95 66 - 0 tel
www.cyberbond.de



Curbell Plastics is a proud supplier of Cyberbond materials.