

OPTIX FLEXILUME SPECIALTY FILM

DESCRIPTION

OPTIX Flexilume film is best used as an overlay film for lenses or louvers or as contour inserts with perforated metals, profiles or reflecting surfaces.

This thin, flexible film (0.020") is easily cut or sheared. Available in clear or white impact acrylic, OPTIX Flexilume features a matte/smooth finish, excellent uniformity, and offers 93% transmission for clear, 62% transmission for white.

Standard sheet available as well as custom sizes.

NOTICE

Plaskolite assumes no responsibility for suitability of luminaires and applications. The use of lenses near and above 70°C temperatures with high UV output light sources will cause degradation of the material.

Material

Up-to-date and detailed material specifications can be found in the Resources section of our website at www.plaskolite.com

Ordering Information

For customer sizes, samples, pricing and delivery please call **800-848-9124**

Item No	Description	Thickness	Dimensions	Light Transmission (±3%)	Packaging
S82410-1	Impact Acrylic Clear	0.020″	50″x 50″	93%	500/pallet
S82409-1	Impact Acrylic Clear	0.020"	50"x 60"	93%	500/pallet
S82400-1	Impact Acrylic White	0.020″	50″x 50″	62%	500/pallet
S82408-1	Impact Acrylic White	0.020″	50″x 60″	62%	500/pallet

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control. We recommend that the prospective user determines the suitability of our materials and suggestions before adopting them on a commercial scale.



400 W Nationwide Blvd, Suite 400 Columbus, OH 43215 800.848.9124 • Fax: 877.538.0754 plaskolite@plaskolite.com www.plaskolite.com

