

Royalite® R57

Fire-rated sheet

CURBELL
PLASTICS

1-888-CURBELL

www.curbellplastics.com

Curbell Plastics is a proud supplier of Spartech® Materials

Product Description

Royalite® R57 thermoplastic sheet is a fire-rated, rigid PVC/ABS product specifically developed to meet Federal Aviation Administration requirements. It passes FAR 25.853 (a)(ii) at 0.047" and above. It is lightweight with very high impact strength, high tensile strength, stiffness and excellent formability.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.18 - 1.26
Tensile Strength	ASTM D-638	4,800 psi
Flexural Strength	ASTM D-790	7,700 psi
Flexural Modulus	ASTM D-790	280,000 psi
Izod Impact (Notched) 72°F	ASTM D-256	8.0 ft-lbs/in
Izod Impact (Notched) -20°F	ASTM D-256	1.6 ft-lbs/in
Rockwell Hardness (R Scale)	ASTM D-785	93
Heat Deflection Temperature (@264 psi - annealed)	ASTM D-648	175°F
Motor Vehicle Safety Standard	FMVSS 302	Passes
Flammability - Vertical Burn - 12 second	FAR 25.853 (a)(ii)	Passes @ 0.047"

**All values based on 0.125" unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**