



THE IDEAL COMBINATION OF DURABILITY, FORMABILITY AND STRENGTH

Utility grade ABS (Acrylonitrile Butadiene Styrene) sheet is extruded with the highest quality regrind and 100% virgin cap. ABS is stocked with one side Haircell and the other smooth, with gauges available from 0.060" - 0.236". It has outstanding formability, high impact strength, and durability.

Custom color matching and sizes available

FEATURES

- » Outstanding molding and fabrication
- » Rigid and creep resistant
- » Run to size - 3000 pound minimum

APPLICATIONS

- » Automotive
- » Dunnage
- » Containers

| Item # | Colors | Pattern/Textures | Masking | Thickness (in.) | Size (in.) | Sq. Ft. | Skid Qty. |
|----------|--------|------------------|---------|-----------------|------------|---------|-----------|
| ABS2103C | White | Haircell/Smooth | None | 0.060 | 48 x 96 | 32 | 125 |
| ABS9900A | Black | Haircell/Smooth | None | 0.060 | 48 x 96 | 32 | 125 |
| ABS2104C | White | Haircell/Smooth | None | 0.093 | 48 x 96 | 32 | 75 |
| ABS9901A | Black | Haircell/Smooth | None | 0.093 | 48 x 96 | 32 | 75 |
| ABS2105C | White | Haircell/Smooth | None | 0.118 | 48 x 96 | 32 | 60 |
| ABS9902A | Black | Haircell/Smooth | None | 0.118 | 48 x 96 | 32 | 60 |
| ABS2106C | White | Haircell/Smooth | None | 0.177 | 48 x 96 | 32 | 40 |
| ABS9903A | Black | Haircell/Smooth | None | 0.177 | 48 x 96 | 32 | 40 |
| ABS2107C | White | Haircell/Smooth | None | 0.236 | 48 x 96 | 32 | 30 |
| ABS9904A | Black | Haircell/Smooth | None | 0.236 | 48 x 96 | 32 | 30 |

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control. We recommend that the prospective user determines the suitability of our materials and suggestions before adopting them on a commercial scale.

PLASKOLITE

400 W Nationwide Blvd, Suite 400
Columbus, OH 43215
800.848.9124 • Fax: 877.538.0754
plaskolite@plaskolite.com
www.plaskolite.com

