

DuPont[™] Vespel[®] Precision Parts for the Aerospace Industry


Solving the toughest sealing, wear and friction challenges in mission-critical applications



Contents

Why DuPont [™] Vespel [®] ?	3
Technical support, Every step of the way	3
The Value of Vespel Parts in Aerospace	4
DuPont [™] Vespel [®] Parts and Shapes	4
DuPont [™] Vespel [®] Parts in Engine Solutions	5
DuPont [™] Vespel [®] Parts in Aircraft Applications	5
DuPont [™] Vespel [®] Parts in Space Applications	6
Bushing & Thrust Washers	6
Compressor Shrouds	7
Abraidable High Temperature Seals	7
Bumpers, Wear Pads, & Wear Strips	8
Wear Strips for Fan Blade Dovetail Root Surface	8
V-Grooves	9
Tube Clamps and Brackets	9
Thrust Reverser Components	10
Self Locking Fasteners	10
Insulators	11

Why DuPont[™] Vespel[®]?



Your partner through design, development and production

 \checkmark

Solution partner of choice

 \checkmark

Core values - safety, sustainability and ethics

•

Proven quality

 \checkmark

Known for delivering innovative material technologies


World class technical support

Culture drives quality and continuous improvement

 \checkmark

Proven service for more than 50 years in aircraft engines and systems


Technical support, every step of the way...



Vespel Parts in Aerospace Enable



DuPont[™] Vespel[®] Parts And Shapes



Compression

DuPont[™] Vespel[®] Engine Solutions


Improving performance, extending life, saving weight & lowering costs

Compressor

- Stator Vane Bushings
- Bumpers & Wear Pads
- Abraidable Seals
- Main Rotor Bumper Bearing
- Composite Shrouds

Fan •

- Fan Blade Root Wear Strips
- Abraidable Seals
- Blade Spacers




Externals

- Composite Tube Clamps
- Duct Seals
- Valve Seals
- Bumper & Wear Pads
- Actuation Arm Bearings
- Bellcrank Bushings
- Locking Fasteners
- Insulators
- Spline Adaptors

Combustor & Nozzle

- Augmenter Flaps
- Nozzle Bushings

DuPont[™] Vespel[®] Aircraft Applications



• Wear Pads and Wear Strips

Vespel.com | 5

DuPont[™] Vespel[®] Space Applications

Performance and stability at low temperatures with low outgassing and radiation resistance

Satellite and Spacecraft

- Camera lens retainers & centering rings
- Seals
- Locking fasteners
- Bearings
- Bushings



- Valve components
- Thermal blanket clips
- Electrical insulators
- Thermal isolators
- Radomes



Bushing & Thrust Washers

Low cost, low friction, long life bearing solutions



Application Challenges

- High temperature
- Wear resistance
- Low friction bearing
- Tight sealing



Features:

- High thermal oxidative stability
- Low coefficient of friction
- Excellent wear resistance
- CTE well matched to mating metal components

DuPont[™] Vespel[®] Material Solutions: • Numerous SCP, CP, ASB, and SP grades




- Weight savings vs. metal bushings
- · Protects expensive mating metal vanes and case from wear
- Efficient compressor operation
- Long life









Compressor Shrouds



Application Challenges

- High Temperature
- Wear Resistance
- Low Friction Bearing

• SCP-5050, ASB-0826

Tight Sealing



DuPont[™] Vespel[®] Material Solutions:



Features:

- High Thermal Oxidative Stability
- Low Coefficient of Friction
- Excellent Wear Resistance
- CTE well matched to mating metal parts

Benefits:

- Weight savings vs metal shrouds with bushings
- Protects expensive mating metal vanes and case from wear
- Efficient compressor operation
- Fewer parts to manage and assemble
- Long Life



Abraidable High Temperature Seals




Application Challenges

- Zero clearance seal
- Chemical / environmental compatibility
- Durable in harsh environment •
- Capable to 600 °F/315 °C



DuPont[™] Vespel[®] Material Solutions:

SF-0920, SF-0930, SF-0940







Features:

- · Closed cell foam for excellent sealing and compatibility
- Capable of holding close tolerances
- Multiple densities available
- Survives temperatures to over 600 °F/315 °C and will not burn

- Improved compressor/fan efficiency due to near zero clearance seal
- Lower cost than typical honeycomb structures
- No treating required for mating blade tips
- · Lightweight, durable designs.

Bumpers, Wear Pads, & Wear Strips

Eliminate metal-to-metal wear



Application Challenges

- Wear resistance
- Low friction
- Strength



Features:

- High resistance to wear
- Low friction surfaces
- Broad geometry and material options


Benefits:

- Improved component life
- Reduced actuation force requirements
- Design flexibility assembly options
- System weight savings
- Protects expensive case from wear



DuPont[™] Vespel[®] Material Solutions:

• SP-21, SCP-5050, CP-0301, CP-0664



Wear Strips for Fan Blade Dovetail Root Surface

DuPont[™] Vespel[®] Material Solutions:



Application Challenges

- High loads
- Low friction
- Tight thickness tolerance
- Wear resistance






Features:

• CP-0664

- High compressive strength
- Coefficient of friction <0.1
- Wear resistance



- Reduces blade stress
- Protects expensive blades from wear
- Controlled, predictable, consistent friction for blade seating
- Corrosion barrier
- Assembly protection



V-Grooves

Eliminate metal-to-metal wear



Application Challenges

- Wear resistance
- Low friction
- Sheer strength / impact resistance
- Corrosion resistance
- Field maintenance



DuPont[™] Vespel[®] Material Solutions:

• CP-0664




Features:

- High resistance to wear
- Low friction surfaces
- Broad geometry options



Benefits:

- Improved component life
- Design flexibility assembly options
- Protects expensive components from wear
- Durability



Tube Clamps and Brackets

Save weight over metal alternatives



Application Challenges

- Light weight
- Vibration dampening
- Alignment
- Strength



DuPont[™] Vespel[®] Material Solutions:

• CP-0301, CP-2020




Features:

- Low density
- High strength
- Meets AS1974 vibratory test requirements



- Delivers >40% weight savings over metal clamps
- High strength
- Forgiving to misalignment
- Improved ease of maintenance







Thrust Reverser Components

Low friction, high load capable solutions



Application Challenges

- High loads
- \cdot Low friction across operating conditions
- Chemical / environmental compatibility
- Wear resistance



DuPont[™] Vespel[®] Material Solutions:

• CP-0664 and ASB grades



Features:

- High compressive strength
- Coefficient of friction <0.1
- Wear resistance



Benefits:

- Controlled, predictable, low friction from first cycle on and across operating environments
- Reliable, proven performance
- Lightweight, durable designs.



Self Locking Fasteners

Reusable Torque Retention




Application Challenges

- Provide torque retention to threaded fastener
- High temperature capable
- Reusable with same torque retention



DuPont[™] Vespel[®] Material Solutions:

• SP-1 and SCP-5000





Features:

- Strength and toughness
- Thermal endurance
- Creep resistant

- Meets torque retention requirements
- Reusable with consistent torque retention
- Integrates with metal threads in nuts and bolts
- Proven performance in critical aerospace systems
- Withstands high vibration when placed on external thread

Insulators

Reusable Torque Retention



Application Challenges

- Electrical or thermal insulation
- Loading and vibrational loading
- Environment temperature



Features:

- Insulative properties
- Fabricate to tight tolerances
- Material toughness
- Lighter than ceramics
- Thermal endurance



DuPont[™] Vespel[®] Material Solutions:

• SP-1, SCP-5000, SF-0920, SF-0930, SF-0940



- Cost savings
- Weight savings
- Thermal endurance versus engineered plastics



Our primary focus is your success

- The DuPont Support Team assigned to your project is uniquely qualified to understand your design needs
- · Dedicated to meeting, and exceeding, your quality requirements
- Experienced with aerospace systems and procedures
- Focused on 100% on-time delivery
- Devoted to unparalleled performance in the field
- · Vespel® aerospace-specific US manufacturing sites are AS9100D certified





1-888-CURBELL

www.curbellplastics.com

Curbell Plastics is an Authorized Distributor of DuPont[™] Vespel[®] Parts and Shapes.

Visit us at Vespel.com

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in one event a guarantee of achieving any specific results. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont[®], the DuPont Oval Logo, and all trademarks and service marks denoted with [™], SM or [®] are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2023 DuPont.