

## Prime Impax™ General Purpose Polystyrene

Our Prime Impax 450 (PI450) is our general purpose grade of High Impact Polystyrene.

**Provides good toughness, stiffness, and impact strength.**

### Customization

Our PI450 material can be made of FDA compliant polystyrene. Since it is an amorphous thermoplastic material, it is relatively easy to process in extrusion and thermoforming. The mold shrink is .003-.006 in./in. It can be formed on aluminum, ceramic, fiberglass, epoxy, and even wood tools.

PI450 can be color matched to meet your specific requirements through our vertical integration with Primex Color, Compounding & Additives.

### Sustainability

Sustainability includes considering the product's circularity or end of life during the design of the finished product. Prime Impax 450 is a polystyrene (recycle code 6) that can be recycled as a post-industrial or post-consumer product. Contact your Primex Territory Business Manager or check with local recycling facilities to determine where it is collected and recycled.

**Primex Sustainability: A better tomorrow, starting today!**



# Prime IMPAX™ 450 | Data Sheet

Prime Impax 450 is a formulated High Impact Polystyrene. It provides good toughness, stiffness, and impact strength. It is designed to meet a wide variety of product applications and is one of the most versatile and inexpensive materials we supply.

## Applications

Some PI450 applications include thermoformed trays, building products, displays, furniture, and computer products. With a GPPS (crystal) cap, it is also ideal for wall surrounds, bathtubs, and other interior applications such as cabinet drawer silverware holders.

## Finishing

PI450 can be fabricated by drilling, routing, sawing, die and/or laser cut. Mechanical fasteners may be used as well as chemical bonding and sonic welding. We provide PI450 in sheet or roll stock and are capable of holding extremely tight tolerances by either square cutting or slitting.

## Colors, Textures, and Capabilities

PI450 is offered in thicknesses of .010-.400 and widths of up to 120". Textures available include; smooth, matte, Seville, RM, HC, Calf Grain, Levant, FL/HC, and even flocked.



Prime IMPAX 450	Very High	High	Avg.
Impact Strength		*	
Low Temperature Impact Strength			*
Tensile Strength		*	
Flexural Modulus		*	
Heat Deflection Temperature			*

**CURBELL**  
PLASTICS

1-888-CURBELL

[www.curbellplastics.com](http://www.curbellplastics.com)

Curbell Plastics is a proud supplier of Primex materials.

**PRIMEX**  
A subsidiary of GDC Corporation Inc.

800.222.5116 | [primexplastics.com](http://primexplastics.com)

Notice: All statements, information, and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation of warranty that such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required.